

TW218Ba

Dual 18" Active Subwoofer

DESCRIPTION

Portable and installed wooden loudspeaker used in applications including sound reinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc. Both active and passive version deliver extraordinary performance at unmatched value.



FEATURES

- Light weight powered 2x18" subwoofer
- 4500W continuous Class D power module
- Strong power penetrating with impact.
- Switching power supply design
- Favorable power module protection system.
- Superior heat dissipation to allow long-time full loaded working.
- Master volume, high cut, phase select, power / peak indication available
- Computer aided design to optimise frequency and phase response
- Combine with any TW or T-series high power speaker for extended full range frequency, high quality music reproduction
- NEUTRIK PowerCON input and output power supply connector
- Power coated protective grill
- Durable Polyurethane textured base paint

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	40Hz-200Hz
	Max SPL @ 1m:	132dB/138dB(PEAK)
Transducers	Woofer:	2 x 18" LF
Input/Output section	Input Connectors:	Input: 1 x XLR; Output: 1 x XLR
Power section	Total Power:	4500W(RMS);
	Nominal Impedance (Ohm):	4Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Physical specifications	Cabinet/Case Material:	Plywood
	Handles:	6 x Wooden handles
	Grille:	Powder coated grill
	Color:	Black
Size	Dimension (W x D x H):	567 x 786 x 1075mm / (22.3 x 30.9 x 42.3in)
	Package Dimensions (W x D x H):	1185 x 895 x 685mm / (46.7 x 35.2 x 27in)
Weight	Net Weight:	86 kg / 189.6 lb
	Gross Weight:	91 kg / 200.6 lb