

TW215

Dual 15" Two Way Full Range Speaker

DESCRIPTION

Portable and installed loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc. Both active and passive version deliver extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- Speakon input connectors
- Integrated pole mount adaptor at bottom
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Suitable for use as a main system with or without sub speaker augmentation
- Powder coated protective grill
- Durable Polyurethane textured base paint

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	45Hz-18kHz
	Max SPL @ 1m:	128dB/134dB(PEAK)
	Dispersion (H x V):	50° x 55°
Transducers	Compression driver:	1 x 3" Compression Driver
	Woofer:	2 x 15" LF
Input/Output section	Sensitivity (1W @ 1m):	101dB
Processor section	Crossover frequencies:	1.6kHz
Power section	Total Power:	500W(RMS); 1000W(MUSIC); 2000W(PEAK);
	Nominal Impedance (Ohm):	4Ω
Physical specifications	Cabinet/Case Material:	Plywood
	Hardware:	Three-point lifting
	Handles:	6 x Wooden handles
	Grille:	Cabinet coated by Polyurethane paint; grille is powder coated
	Color:	Black
Size	Dimension (W x D x H):	520 x 520 x 1090mm / (20.5 x 20.5 x 42.9in)
	Package Dimensions (W x D x H):	650 x 650 x 1240mm / (25.6 x 25.6 x 48.8in)
Weight	Net Weight:	52 kg / 114.6 lb
	Gross Weight:	59.5 kg / 131.2 lb