

TH315/64

15" 3-Way full Range Speaker

DESCRIPTION

TH Series is designed for permanent installation within medium to large Theatre venue sound reinforcement system applications, the outstanding mid/high performance ensures clean, clear and natural sound throughout the listening environment, even at high SPL.



FEATURES

- High SPL and high sensitivity three way full range system
- 1x6"MF 1x1.75"HF compressed driver,1X15"LF
- High strength cabinet structure
- Powder coated grill
- Computer aided design to optimize frequency and phase response
- Durable Polyurethane textured bas paint
- suitable for theatre ,television studio, multi-functional room and performance studio



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	LF: 60Hz-800kHz; MF/HF: 280Hz-20kHz
	Max SPL @ 1m:	Bi-amp: LF 124dB/130dB(PEAK); MF/HF 122dB/128dB(PEAK); Tri-amp: LF 124dB/130dB(PEAK);
	Dispersion (H x V):	TH315/64: 60°x 40° TH315/94: 90°x 40°
Transducers	Compression driver:	1 x 1.75" HF
	Midrange:	1 x 6" MF
	Woofer:	1 x 15" LF
Input/Output section	Input Connectors:	1 x NL8, 8-way binding post
	Sensitivity (1W @ 1m):	Bi-amp: LF 100dB; MF/HF 108dB; Tri-amp: LF 100dB; MF 108dB; HF 110dB;
Power section	Total Power:	LF: 400W; MF: 120W; HF: 50W(RMS);
	Nominal Impedance (Ohm):	8Ω
Physical specifications	Hardware:	12 x M10
	Color:	Black
Size	Dimension (W x D x H):	520 x 520 x 980mm / (20.5 x 20.5 x 38.6in)
	Package Dimensions (W x D x H):	630 x 630 x 1080mm / (24.8 x 24.8 x 42.5in)
Weight	Net Weight:	49.5 kg / 109.1 lb
	Gross Weight:	53.5 kg / 117.9 lb