

CSR10L

10" Two-way full range speaker

DESCRIPTION

The Beta Three® Professional theater speakers are mainly suitable for all sizes cinema digital stereo system/theater/meeting room and multi-function stage sound reinforcement system. Using newest computer design simulation technology, integrating newest materials to develop and produce the speaker components. Excellent sound quality is recognized by the many professors. Adopt the latest efficient protection circuit to adapt for different environment.



FEATURES

- Two transducers two- way full range
- One 10" big power woofer
- One 44mm compression driver
- Frequency response (-3dB):60Hz-20kHz
- Sensitivity 94dB, Maximum SPL 124dB
- Rated power 250W, peak power 500W
- 4xM6 lifting point on the back, 1xM8 lifting point at each side



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	60Hz-20kHz
	Max SPL @ 1m:	124dB/130dB(PEAK)
	Dispersion (H x V):	85° x 85°
Transducers	Compression driver:	1 x 44mm HF
	Woofer:	1 x 10" LF
Input/Output section	Input Connectors:	Spring clip
	Sensitivity (1W @ 1m):	94dB
Processor section	Crossover frequencies:	1.6kHz
Power section	Total Power:	250W(RMS); 500W(MUSIC); 1000W(PEAK);
	Nominal Impedance (Ohm):	8Ω
Physical specifications	Color:	Black
Size	Dimension (W x D x H):	556 x 256 x 455mm / (21.9 x 10.1 x 17.9in)
	Package Dimensions (W x D x H):	545 x 345 x 660mm / (21.5 x 13.6 x 26in)
Weight	Net Weight:	15 kg / 33.1 lb
	Gross Weight:	17.6 kg / 38.8 lb