

CTM1000B

10" Two-way Full Range Active Speaker

DESCRIPTION

The portable and installed plastic loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Medium-sized Conference Rooms, Multi-functional Hall, Church, Auditorium Performance Places etc. The CTM Active Series delivers extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- 1 x 10" high power transducer
- 1 x 25mm diaphragm compression driver
- Heavy duty protective grill and high strength polypropylene precision Injection molded
- Built-in Class D power amplifier module
- Master volume, Bass and Treble control
- Switchable between Mic and Line input
- Bluetooth connection available

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	60Hz-18kHz
	Max SPL @ 1m:	111dB/117dB(PEAK)
	Dispersion (H x V):	120° x 120°
Transducers	Compression driver:	1 x 25mm Compression Driver
	Woofer:	1 x 10" LF
Input/Output section	Input Connectors:	1 x XLR
Power section	Total Power:	150W+50W(RMS);
	Nominal Impedance (Ohm):	8Ω
	Voltage range:	AC 100V-240V~, 50Hz/60Hz
Physical specifications	Cabinet/Case Material:	Polypropylene Injection Molding
	Hardware:	3 Hanging point
	Handles:	Plastic Handles
	Grille:	Powdered Coated Grill
	Color:	Black
Size	Dimension (W x D x H):	325 x 308 x 478mm / (12.8 x 12.1 x 18.8in)
	Package Dimensions (W x D x H):	380 x 360 x 540mm / (15 x 14.2 x 21.3in)
Weight	Net Weight:	10.4 kg / 22.9 lb
	Gross Weight:	11.4 kg / 25.1 lb