β_{3}

TW6

Dual 6" Two Way Full Range Speaker

DESCRIPTION

Portable and installed active loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc. Both active and passive version deliver extraordinary performance at unmatched value.

FEATURES

- High output SPL and sensitivity
- Speakon input connectors
- Integrated pole mount adapter at bottom
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Suitable for use as a main system with or without sub speaker augmentation
- Powder coated protective grill
- Durable Polyurethane textured base paint



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	70Hz-19kHz
	Max SPL @ 1m:	104dB/110dB(PEAK)
	Dispersion (H x V):	90° x 50°
Transducers	Compression driver:	1 x 1" HF
	Woofer:	2 x 6" LF
Input/Output section	Input Connectors:	Wire clip
	Sensitivity (1W @ 1m):	92dB
Power section	Total Power:	160W(RMS); 320W(MUSIC); 640W(PEAK);
	Nominal Impedance (Ohm):	8Ω
Physical specifications	Color:	Black
Size	Dimension (W x D x H):	191 × 230 × 541mm / (7.5 × 9.1 × 21.3in)
	Package Dimensions (W x D x H):	460 × 320 × 620mm / (18.1 × 12.6 × 24.4in)
Weight	Net Weight:	11.5 kg / 25.4 lb
	Gross Weight:	26 kg / 57.3 lb