
β_3

EX212Ba

12" Compact Active Low Frequency Speaker

DESCRIPTION

The EX212Ba is a compact active low frequency speaker system. It is used in large and medium-sized places requiring high sound pressure and high reliability. It consists of two 12-inch low-frequency drivers and a power amplifier module.



FEATURES

- Dual 12" high power activer subwoofer
- 4" Voice Coil woofers deliver low distortion, high fidelity output
- 800 Watt Class-D Amplifier with universal power supply
- Low profile design, vertical and horizantal stack with M20
- Easily connect to EX system



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	40Hz-100Hz
	Max SPL @ 1m:	114dB/120dB((PEAK)
Transducers	Woofer:	2 x 12" woofer
Input/Output section	Input signal:	Balanced $20 k\Omega$, Unbalanced $10 k\Omega$
	Input Connectors:	2 x Combo input, 2 x XLR output
Power section	Total Power:	800W(RMS); 1600W(MUSIC); 3200W(PEAK);
	Nominal Impedance (Ohm):	4Ω
	Voltage range:	AC 100V-240V~, 50Hz/60Hz
Physical specifications	Cabinet/Case Material:	Plywood
	Handles:	4 × Wooden handle
	Grille:	White Polyurethane painting for cabinet & White Powder coated grille.
	Color:	White
Size	Dimension (W x D x H):	460 x 520 x 720mm / (18.1 x 20.5 x 28.3in)
	Package Dimensions (W x D x H):	630 x 580 x 850mm / (24.8 x 22.8 x 33.5in)
Weight	Net Weight:	42 kg / 92.6 lb
	Gross Weight:	45 kg / 99.2 lb