

MU408

4" Two Way Full Range Column Speaker

DESCRIPTION

MU408 installed line array column loudspeakers are used in applications including sound reinforcement for Houses of Worship, Events, Theme Parks, Transit Terminals and shopping malls etc. The T series delivers extraordinary performance where high speech intelligibility and natural sounding music is required at unmatched value.



FEATURES

- Vertical line array of 8 x 4" LF driver
- 44mm compression driver loaded with wave guide
- Frequency response 80Hz-18kHz(-3dB)
- Sensitivity 92dB, Max SPL 116dB
- 150x 30 degree controlled coverage pattern
- Birch plywood construction
- Durable Polyurethane textured base paint
- Quick install U bracket included with multiple mounting points provided
- Designed for high speech intelligibility and natural sounding music
- Optional MU408 hanging hardware



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	80Hz-18kHz
	Max SPL @ 1m:	116dB/122dB(PEAK)
	Dispersion (H x V):	150° x 30°
Transducers	Compression driver:	1 x 44mm HF
	Woofer:	8 x 4" LF
Input/Output section	Input Connectors:	4-screw termina, 2 x XLR
	Sensitivity (1W @ 1m):	92dB
Processor section	Crossover frequencies:	2kHz
Power section	Total Power:	240W(RMS); 480W(MUSIC); 960W(PEAK);
Physical specifications	Cabinet/Case Material:	15mm birch plywood
	Hardware:	6 x M8
	Grille:	White Polyurethane painting for cabinet & White Powder coated grille.
	Color:	White
Size	Dimension (W x D x H):	164 x 1138 x 233mm / (6.5 x 44.8 x 9.2in)
	Package Dimensions (W x D x H):	305 x 1240 x 243mm / (12 x 48.8 x 9.6in)
Weight	Net Weight:	16.7 kg / 36.8 lb
	Gross Weight:	18.2 kg / 40.1 lb